PROFESSIONAL



GIGA X3 Flexibility in the top class





Benefits

- 4,3" touchscreen colour display
- Precision ceramic disc grinder with Automatic Grinder Adjustment (A.G.A.)
- Speed function thanks to additional hot water bypass
- 2 thermoblocks and 2 pumps
- Compatible with Payment Connect

Recommended accessories

- Glass Cup Warmer
- Cool Control 2,51
- Cool Control 1
- Wireless Transmitter for the Cool Control
- Lockable bean container
- Coffee grounds disposal/ drip drain set
- Payment Connect
- Accessory set for milk systems HPX3
- Coffee to Go furniture range
- Data Communicator

Areas of use

- Office floor solutions
- Seminar/conference facilities
- Breakfast room
- Catering
- Coffee to Go

Recommended maximum daily output 150 cups

The GIGA X3 allows JURA to impressively demonstrate Swiss innovation and professionalism down to the very last detail. Anywhere where a capacity of up to 150 cups is the order of business, the machine impresses users with its quality, functionality and reliability. Coupled with top performance in every respect, this results in a high-tech automatic coffee machine that is ideally tailored to the requirements of large offices, the breakfast, seminar and conference venue sectors as well as self-service areas.

The GIGA X3 features the new payment and management system Pocket Pilot 2.0. Pocket Pilot 2.0 allows both cashless payment and central machine monitoring without any additional infrastructure. This is made possible by Payment Connect, which is easy to install in the GIGA X3. This web-based system is free and does not require any software to be installed. Once you have created an account for JURA Pocket Pilot 2.0, you have access to a comprehensive, user-friendly management system.





GIGA X3 Technical overview

Number of specialities	32
Speed function	
Automatic Grinder Adjustment (A.G.A.)	
Active bean monitoring	
Automatic switchover from milk to milk foam	
Transmitter supplied as standard	Smart Connect
URA coffee machine standards	
Pulse Extraction Process (P.E.P.®)	
One-Touch function	
Variable brewing unit	5 – 16 g
Grinder	Electronically adjustable ceramic disc grinder
High-performance pump, 15 bar	2
Thermoblock heating system	2
Fluid systems	2
Milk system/interchangeable milk spout	HP3/CX2
Powder chute for ground coffee	
Aroma preservation cover	-
Operating and programming standards Compatible with J.O.E.® Compatible with Payment Connect	:
Operating and programming standards Compatible with J.O.E.®	•
Operating and programming standards Compatible with J.O.E.® Compatible with Payment Connect Rotary Switch Display	
Operating and programming standards Compatible with J.O.E.® Compatible with Payment Connect Rotary Switch Display Store, copy and personalise products	4,3" touchscreen
Operating and programming standards Compatible with J.O.E.® Compatible with Payment Connect Rotary Switch Display	4,3" touchscreen colour display
Operating and programming standards Compatible with J.O.E.® Compatible with Payment Connect Rotary Switch Display Store, copy and personalise products Programmable and individually adjustable	4,3" touchscreen colour display
Operating and programming standards Compatible with J.O.E.® Compatible with Payment Connect Rotary Switch Display Store, copy and personalise products Programmable and individually adjustable amount of water Programmable and individually adjustable	4,3" touchscreen colour display
Operating and programming standards Compatible with J.O.E.® Compatible with Payment Connect Rotary Switch Display Store, copy and personalise products Programmable and individually adjustable amount of water Programmable and individually adjustable coffee strength Programmable amount of milk/milk foam Programmable milk/milk foam temperature	4,3" touchscreen colour display
Operating and programming standards Compatible with J.O.E.® Compatible with Payment Connect Rotary Switch Display Store, copy and personalise products Programmable and individually adjustable amount of water Programmable and individually adjustable coffee strength Programmable amount of milk/milk foam Programmable amount of milk/milk foam Programmable milk/milk foam temperature Programmable brewing temperature	 4,3" touchscreen colour display 10 levels 10 levels 3 levels
Operating and programming standards Compatible with J.O.E.® Compatible with Payment Connect Rotary Switch Display Store, copy and personalise products Programmable and individually adjustable amount of water Programmable and individually adjustable coffee strength Programmable amount of milk/milk foam Programmable amount of milk/milk foam Programmable brewing temperature Programmable temperature of hot water	 4,3" touchscreen colour display 10 levels 10 levels
Operating and programming standards Compatible with J.O.E.® Compatible with Payment Connect Rotary Switch Display Store, copy and personalise products Programmable and individually adjustable amount of water Programmable and individually adjustable coffee strength Programmable amount of milk/milk foam Programmable amount of milk/milk foam Programmable milk/milk foam temperature Programmable brewing temperature	 4,3" touchscreen colour display 10 levels 10 levels 3 levels
Operating and programming standards Compatible with J.O.E.® Compatible with Payment Connect Rotary Switch Display Store, copy and personalise products Programmable and individually adjustable amount of water Programmable and individually adjustable coffee strength Programmable amount of milk/milk foam Programmable milk/milk foam temperature Programmable brewing temperature Programmable temperature of hot water Intelligent Pre-Brew Aroma System	 4,3" touchscreen colour display 10 levels 10 levels 3 levels 3 levels
Operating and programming standards Compatible with J.O.E.® Compatible with Payment Connect Rotary Switch Display Store, copy and personalise products Programmable and individually adjustable amount of water Programmable and individually adjustable coffee strength Programmable amount of milk/milk foam Programmable amount of milk/milk foam Programmable brewing temperature Programmable temperature of hot water Intelligent Pre-Brew Aroma System with optional deactivation	 4,3" touchscreen colour display 10 levels 10 levels 3 levels 3 levels

Intelligent Water System (I.W.S.)	
CLARIS filter cartridge	CLARIS Pro Smart maxi / CLARIS Pro Smart
One-Touch milk system cleaning (automatic)	
Integrated rinsing, cleaning and descaling programme	
Monitored drip tray	
JURA hygiene: TÜV-certified	•
Energy standards	
Energy Save Mode (E.S.M.®)	
Zero-Energy Switch or power switch	
Programmable switch-off time	
Programmable switch-on/switch-off time	-
Design and materials	
Alu Frame Design [©] 3 mm	
Centre panel in Piano Black	
Amber/white cup illumination Maximum hourly output Number of cups per bour (as per DIN 18872-2)	
Maximum hourly output Number of cups per hour (as per DIN 18873-2) Espresso (1×/2×)	96/142
Maximum hourly output Number of cups per hour (as per DIN 18873-2) Espresso (1×/2×) Coffee (1×/2×)	96/142 66/76
Maximum hourly output Number of cups per hour (as per DIN 18873-2) Espresso (1×/2×) Coffee (1×/2×) Cappuccino (1×/2×)	96/142 66/76 76/110
Maximum hourly output Number of cups per hour (as per DIN 18873-2) Espresso (1×/2×) Coffee (1×/2×)	96/142 66/76
Maximum hourly output Number of cups per hour (as per DIN 18873-2) Espresso (1×/2×) Coffee (1×/2×) Cappuccino (1×/2×) Hot water	96/142 66/76 76/110 104
Maximum hourly output Number of cups per hour (as per DIN 18873-2) Espresso (1×/2×) Coffee (1×/2×) Cappuccino (1×/2×) Hot water In figures Height-adjustable dual spout	96/142 66/76 76/110 104 70 – 159 mm
Maximum hourly output Number of cups per hour (as per DIN 18873-2) Espresso (1×/2×) Coffee (1×/2×) Cappuccino (1×/2×) Hot water In figures Height-adjustable dual spout Height-adjustable hot-water spout	96/142 66/76 76/110 104 70 – 159 mm 69 – 165 mm
Maximum hourly output Number of cups per hour (as per DIN 18873-2) Espresso (1×/2×) Coffee (1×/2×) Cappuccino (1×/2×) Hot water In figures Height-adjustable dual spout Height-adjustable hot-water spout Water tank capacity	96/142 66/76 76/110 104 70 – 159 mm 69 – 165 mm 51
Maximum hourly output Number of cups per hour (as per DIN 18873-2) Espresso (1×/2×) Coffee (1×/2×) Cappuccino (1×/2×) Hot water In figures Height-adjustable dual spout Height-adjustable hot-water spout Water tank capacity Bean container holding capacity	96/142 66/76 76/110 104 70 – 159 mm 69 – 165 mm 51 1kg
Maximum hourly output Number of cups per hour (as per DIN 18873-2) Espresso (1×/2×) Coffee (1×/2×) Cappuccino (1×/2×) Hot water In figures Height-adjustable dual spout Height-adjustable hot-water spout Water tank capacity Bean container holding capacity Coffee grounds container (servings)	96/142 66/76 76/110 104 70 – 159 mm 69 – 165 mm 51 1kg max. 40
Maximum hourly output Number of cups per hour (as per DIN 18873-2) Espresso (1×/2×) Coffee (1×/2×) Cappuccino (1×/2×) Hot water In figures Height-adjustable dual spout Height-adjustable hot-water spout Water tank capacity Bean container holding capacity Coffee grounds container (servings) Cable length	96/142 66/76 76/110 104 70 – 159 mm 69 – 165 mm 51 1 kg max. 40 ca. 1,1 m
Maximum hourly output Number of cups per hour (as per DIN 18873-2) Espresso (1×/2×) Coffee (1×/2×) Cappuccino (1×/2×) Hot water In figures Height-adjustable dual spout Height-adjustable hot-water spout Water tank capacity Water tank capacity Bean container holding capacity Coffee grounds container (servings) Cable length Voltage/Power	96/142 66/76 76/110 104 70 – 159 mm 69 – 165 mm 51 1kg max. 40 ca. 1,1 m 220 – 240 V~/2700
Maximum hourly output Number of cups per hour (as per DIN 18873-2) Espresso (1×/2×) Coffee (1×/2×) Cappuccino (1×/2×) Hot water In figures Height-adjustable dual spout Height-adjustable hot-water spout Water tank capacity Bean container holding capacity Coffee grounds container (servings) Cable length Voltage/Power Current	96/142 66/76 76/110 104 70 – 159 mm 69 – 165 mm 51 1kg max. 40 ca. 1,1 m 220 – 240 V~/2700 10A
Maximum hourly output Number of cups per hour (as per DIN 18873-2) Espresso (1×/2×) Coffee (1×/2×) Cappuccino (1×/2×) Hot water In figures Height-adjustable dual spout Height-adjustable hot-water spout Water tank capacity Bean container holding capacity Coffee grounds container (servings) Cable length Voltage/Power Current Stand-by power	96/142 66/76 76/110 104 70 - 159 mm 69 - 165 mm 51 1kg max. 40 ca. 1,1 m 220 - 240 V~/2700 10A < 0,5 W
Maximum hourly output Number of cups per hour (as per DIN 18873-2) Espresso (1×/2×) Coffee (1×/2×) Cappuccino (1×/2×) Hot water In figures Height-adjustable dual spout Height-adjustable hot-water spout Water tank capacity Water tank capacity Bean container holding capacity Coffee grounds container (servings) Cable length Voltage/Power Current Stand-by power Weight	96/142 66/76 76/110 104 70 - 159 mm 69 - 165 mm 51 1 kg max. 40 ca. 1,1 m 220 - 240 V~/2700 10A < 0,5 W 19 kg
Maximum hourly output Number of cups per hour (as per DIN 18873-2) Espresso (1×/2×) Coffee (1×/2×) Cappuccino (1×/2×) Hot water In figures Height-adjustable dual spout Height-adjustable hot-water spout Water tank capacity Bean container holding capacity Coffee grounds container (servings) Cable length Voltage/Power Current Stand-by power	96/142 66/76 76/110 104 70 - 159 mm 69 - 165 mm 51 1kg max. 40 ca. 1,1 m 220 - 240 V~/2700 10A < 0,5 W





 \square

L

 \neg